

Town Hall™

With Unilock's ever increasing focus on permeable pavers, Town Hall has been designed to satisfy both traditional and permeable installation methods while maintaining a historical worn and distressed appearance.

Colors



Burgundy Red



Burnt Clay



Old Oak



3 Color Blend
Blended on Site



Basalt



Heritage Red



Heritage Clay



Heritage Blend
Blended on Site

Shapes & Sizes



Standard

25 cm x 10 cm x 7 cm

9.75" x 3.75" x 2.75"

Why Choose **ENDURACOLOR^{PLUS}**

This product features EnduraColor™ Plus, a proprietary blended layer of nature's highest performing minerals that never fade. It virtually outperforms any other paver surface when it comes to surface wear, color retention and its ability to repel even the nastiest staining substances. Choosing EnduraColor Plus, will ensure your patio, driveway, outdoor kitchen or pool deck will look like new, even after years of wear and tear.

[Learn About Town Hall](#)

[Town Hall Torture Test](#)

Features

Applications

Borders & Accents

Commercial Vehicular

Pedestrian

Residential Vehicular

Technologies

EnduraColor™ Plus

EnduraColor Plus is the defining difference when it comes to superior wear resistance and color longevity. EnduraColor Plus is not a coating or secondary treatment, but rather a proprietary blended layer of nature's highest performing minerals (which never fade) that have been embedded right into the surface of each stone during the manufacturing process. This ensures that the surface will not fade, crack, peel or delaminate, and the beauty of your project will last a lifetime.

Reala™ Surface Technology

Ultra-realistic textures cast from actual natural stone, brick and cobblestones.


Ultima™ Concrete Technology

For heavy traffic loads, this proprietary manufacturing process creates pavers and walls with up to 4 times the strength of poured concrete.


Surface Texture

Timeworn


Patterns




Town Hall A
Standard (100%)



Town Hall B
Standard (100%)



Town Hall C
Standard (100%)



Town Hall D
Standard (100%)

Packaging

	Sq. Ft. Bndl.	Sq. Ft. Layer	Layers Bndl.	Ln Ft Bndl. Soldier	Lbs Bndl.	Lbs Sec.	Units Bndl.
Standard - Full Bundle	88.41	11.05	8	105.0	2888	361	320
Standard - Half Bundle	44.2	11.05	4	52.5	1444	181	160

Town Hall™ Old Oak, Burgundy Red, Burnt Clay Blend - Sold Separately/Blended on Site

Town Hall™ Heritage Red, Heritage Clay, Basalt Blend - Sold Separately/Blended on Site

Additional Town Hall™ Information

Sold in full or half bundles only on a refundable skid. All measurements are nominal. Important: Textured surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing. Take extra care when using Polymeric Sand with this product. Call for more information.

Important Information

Town Hall Street Pavers combine the timeless beauty of historic clay bricks with the functionality, performance and colorfastness that only EnduraColor Plus pavers from Unilock can deliver. This paver can be used with both permeable and traditional installation methods.

Base Requirement & Bedding Course – standard or open graded paver base specification.

Handling & Installation – A protective pad is required when doing the final paver compaction. Install from multiple pallets for best color distribution.

Accent compatibility

- o all paver applications and can be used as a wall accent.

Jointing Material and Joint Stabilization

- o Good: Ordinary dry joint sand stabilized by a water-based or solvent based joint sand stabilizer sealer

(for impervious installations only)

- o Better:

o Non- pervious - Unicare Polymeric Sand, Techniseal RG+, Alliance XP

o Permeable – Select graded stone chips

- o Best:

o Non- pervious - Alliance Sand – Eurostone or Polymeric Sand MAX

o Permeable – Unilock EasyPro Joint Compound

o Overlays - Alliance Gator Maxx Polymeric Sand

Note:

o Polymeric sand is often installed too high in the joint. Ensure the sand level is lower than the paver surface to allow for a three dimensional appearance.

Sealers

- o Product may be sealed but it is not absolutely required
- o sealers generally decrease the slip resistance of a product
- o Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
 - o Semi-gloss sealers will still appear glossy on this product. Please test a stone to ensure the desired effect.
- o Product must be cleaned before sealing

Cleaners – Any paver cleaner from Unilock, Techniseal, Surebond or BP- Pro is acceptable.

Special note: Other than overlay on concrete stoops and steps, you should have a bedding layer between the pavers and the poured concrete surface to avoid issues with height variance

i All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.