

Hollandstone™

---

## A versatile paver with a wide range of color options

With its wide range of colors, Hollandstone is a favorite for many because of the design flexibility it provides. Available in one size this paver can be laid in various patterns.



---

### Colors



Almond Grove  
New for 2016



Charcoal



Granite



Red



Rustic Red



Sierra



Terra Cotta

---

### Shapes & Sizes



4 x 8 x 2.4  
20 cm x 10 cm x 6 cm  
7.75" x 3.75" x 2.25"



4 x 8 x 3.1  
Special Order  
20 cm x 10 cm x 8 cm  
7.75" x 3.75" x 3"

---

## Design Combinations

The finishing touches to your project lies in the exceptional borders and accents that you incorporate into your landscape features. Looking for more options the pictures featured on the right? Create your own design combinations by clicking the button below!

Create Your Own



---

## Features

### Applications

---


- Borders & Accents
- Commercial Vehicular
- Pedestrian
- Residential Vehicular

### Surface Texture

---


- Standard

## Patterns




**Hollandstone B**

Standard (100%)



**Hollandstone C**

Standard (100%)



**Hollandstone D**

Standard (100%)

## Packaging

	Unit	Sq. Ft.	Sq. Ft.	Layers	Ln Ft Bndl. Soldier	Sq Ft Ln Ft Soldier	Sq Ft Ln Ft Sailor	Units Sq. Ft.	Lbs Bndl.	Lbs Sec.	Units Bndl.
4 x 8 x 2.4	6	106.4	17.73	6	159.4	0.667	0.334	4.57	2789	465	486
4 x 8 x 3.1 Special Order	8	82.5	13.75	6	124	0.665	0.333	4.58	2944	491	378

## Important Information

*Hollandstone is a very popular value paver. The simple lines and patterns make it easy to work with. Add a special look to Hollandstone by incorporating Unigranite or Series 3000 banding and insets.*

**Base Requirement & Bedding Course** – standard paver base specification.

**Handling and Installation**– A protective pad is required when doing the final paver compaction. Both herringbone and linear patterns are common.

### Jointing Material and Joint Stabilization

- Good: ordinary dry joint sand
  - Best: Any Polymeric Sand or ordinary dry joint sand stabilized by a water-based or solvent-based joint sand stabilizer sealer. Important: squeegee water from surface during polymeric sand activation to prevent a white residue from forming.

Special Note: Use Alliance Gator Max Polymeric Sand (overlays)

### Sealers

- Product may be sealed but it is not absolutely required
- Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
- Select type for desired aesthetics.
- Product must be cleaned before sealing

**Cleaners** – Any paver cleaner may be used for color restoration or general cleaning. Follow manufacturer's dilution rates and application procedures.

**i** All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections

should always be made from actual samples.