

Avante Ashlar™

Sorry this product is not available in your region. Click [here](#) to view all products in your area.

Avante Ashlar, another innovative introduction by Unilock, features a unique ashlar design with a random appearance.

Each Avante Ashlar stone unit incorporates several random shapes with varying textures into one module, giving you a unique natural stone appearance. The exclusive “L” shaped design promotes installation accuracy and lock-up integrity.



Colors

Shapes & Sizes

Features

Technologies

EnduraColor™

Two high performance layers are compressed and cured together to provide the highest quality of strength, durability, and everlasting color.

Surface Texture


Flagstone

Applications

Pedestrian

Residential Vehicular

Patterns



Avante Ashlar A

Random Bundle (100%)

Packaging

Additional Avante Ashlar™ Information

Sold in full bundles only. This material is packaged on a refundable skid. Important: Textured surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing. Contact Unilock® for information.

Important Information

Avante Ashlar, another innovative introduction by Unilock, features a unique quarried stone pattern with a random appearance. Each Avante Ashlar stone unit incorporates multiple shapes with varying textures into one module. The exclusive "L" shaped design promotes installation accuracy and lock-up integrity.

Base Requirement & Bedding Course – standard paver or open-graded base specification.

Handling and Installation– A protective pad is required when doing the final paver compaction. Automatic random pattern is generated. Install from several pallets to get best color mixing.

Jointing Material and Joint Stabilization

- Better: Any Polymeric Sand or ordinary dry joint sand stabilized by a water-based or solvent-based joint sand stabilizer sealer. (Joints should be flooded but the paver surface must be squeegeed and/or blown clean).
- Best: Unilock EasyPro™

Sealers

- Product may be sealed but it is not absolutely required
- Unilock Unicare®, Surebond, BP Pro and Techniseal® sealers can be used.
- Select type for desired aesthetics.
- Product must be cleaned before sealing

Cleaners – Any paver cleaner may be used for color restoration or general cleaning. Follow manufacturer's dilution rates and application procedures.

Special note - To avoid issues with height variance, do not use as a direct overlay on concrete.

 All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.