

Stonehenge®

Sorry this product is not available in your region. Click [here](#) to view all products in your area.

Set the foundation for a majestic setting by building your plans around the aged appearance of this paver.

The day after your patio is installed with this paving stone it will look like it's been there for years. That is the true beauty of Unilock's tumbled paving stones. Inviting and natural, this paver features three unit sizes, allowing you to create a random pattern or a fixed pattern that's simple and pleasing to the eye.

Tweet



Colors

Almond Grove

Granite

Sierra



Shapes & Sizes

Design Combinations

The finishing touches to your project lies in the exceptional borders and accents that you incorporate into your landscape features. Looking for more options the pictures featured on the right? Create your own design combinations by clicking the button below!

Create Your Own



Features

Applications

Borders & Accents

Commercial Vehicular


Pedestrian

Residential Vehicular


Surface Texture

Dimpled & Weathered


Patterns




Stonehenge A
 Rectangle (67%)
 Small Square (34%)




Stonehenge B
 Large Square (50%)
 Rectangle (50%)




Stonehenge C
 Large Square (30%)
 Rectangle (47%)
 Small Square (23%)




Stonehenge D
 Large Square (54%)
 Rectangle (37%)
 Small Square (9%)




Stonehenge E
 Large Square (80%)
 Small Square (20%)




Stonehenge F
 Large Square (67%)
 Rectangle (22%)
 Small Square (11%)



Stonehenge G
 Large Square (57%)
 Rectangle (29%)
 Small Square (14%)



Stonehenge H
 Rectangle (100%)



Stonehenge I
 Rectangle (67%)
 Small Square (34%)

Packaging

Additional Stonehenge® Information

The product can be installed dimpled side up or smooth side up.

Important Information

The dimpled surface of Stonehenge adds to the traditional look and feel of this favorite paver. The equilateral unit sizes allow for a myriad of rectilinear design patterns. Stonehenge should be accented or bordered with Unilock Belpasso or Umbriano pavers for a signature design. Ideal for walkways, patios, terraces, driveways and more.

Base Requirement & Bedding Course – standard paver base specification.

Handling and Installation– A protective pad is required when doing the final paver compaction. Both herringbone, random and linear patterns are common.

Jointing Material and Joint Stabilization

- Good: ordinary dry joint sand
 - Best: Any Polymeric Sand or ordinary dry joint sand stabilized by a water-based or solvent-based joint sand stabilizer/sealer. (Joints should be flooded but the paver surface must be squeegeed and/or blown clean).

Special Note: Gator Max Polymeric Sand (overlays)

Sealers

- Product may be sealed but it is not absolutely required
- Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
- Select type for desired aesthetics.
- Product must be cleaned before sealing

Cleaners – Any paver cleaner may be used for color restoration or general cleaning. Follow manufacturer's dilution rates and application procedures.

Special note - To avoid issues with height variance, do not use as a direct overlay on concrete

All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.