

## Eco-Priora™

## Architectural design with engineered performance.

Available in multiple shapes, this new permeable paver is also produced using face-mix technology that will increase the durability of the product and provide better color retention. Custom colors and finishes are available to offer unlimited design possibilities. Combined with a surface infiltration rate of up to 140 inches per hour, Eco-Priora offers both aesthetics and performance.



### Colors



Coffee Creek  
Standard Finish



Coffee Creek  
Tumbled Finish  
Special Order



Granite Blend  
Standard Finish



Granite Blend  
Tumbled Finish  
Special Order



Sierra  
Standard Finish



Sierra  
Tumbled  
Special Order



Autumn Sunset  
Umbriano Finish  
Special Order



Midnight Sky  
Umbriano Finish  
Special Order



Summer Wheat  
Umbriano Finish  
Special Order



Winter Marvel  
Umbriano Finish  
Special Order

## Shapes & Sizes



10 x 10 - Standard  
24 cm x 24 cm x 8 cm  
9.25" x 9.25" x 3"



5 x 10 - Standard  
24 cm x 12 cm x 8 cm  
9.25" x 4.5" x 3"



5 x 5 - Standard  
12 cm x 12 cm x 8 cm  
4.5" x 4.5" x 3"



10 x 10 - Tumbled  
(Special Order)  
24 cm x 24 cm x 8 cm  
9.25" x 9.25" x 3"



5 x 10 - Tumbled  
(Special Order)  
24 cm x 12 cm x 8 cm  
9.25" x 4.5" x 3"



10 x 10 - Umbriano Finish  
(Special Order)  
24 cm x 24 cm x 8 cm  
9.25" x 9.25" x 3"



5 x 10 - Umbriano Finish  
(Special Order)  
24 cm x 12 cm x 8 cm  
9.25" x 4.5" x 3"



5 x 5 - Umbriano Finish  
(Special Order)  
12 cm x 12 cm x 8 cm  
4.5" x 4.5" x 3"

## Design Combinations

The finishing touches to your project lies in the exceptional borders and accents that you incorporate into your landscape features. Looking for more options the pictures featured on the right? Create your own design combinations by clicking the button below!

Create Your Own



## Features

### Applications

---


Borders & Accents

Commercial Vehicular

Pedestrian


Residential Vehicular

### Patterns



**Eco-Priora H**

5 x 10 (50%)  
10 x 10 (50%)



**Eco-Priora E**

5 x 10 (100%)

### Packaging

---

	Unit Thickness	Sq. Ft. Bndl.	Sq. Ft. Layer	Layers Bndl.	Ln Ft Bndl. Soldier	Sq Ft Ln Ft Soldier	Units Sq. Ft.	Lbs Bndl.	Lbs Sec.	Units Bndl.
10 x 10 - Standard, Tumbled or Umbriano Finish (Special Order)	-	86.6	12.37	7	110.2	-	-	3099	443	140
5 x 10 - Standard or Umbriano Finish (Special Order)	-	74.59	10.66	7	96.4	-	-	2669	381	245
5 x 10 - Tumbled (Special Order)	8	74.59	10.66	7	96.4	.785	1.62	2669	381	245
5 x 5 - Standard or Umbriano Finish (Special Finish)	8	74.59	10.66	7	192.9	.785	1.62	2669	381	490

### Special Order - Lead Time Required. Minimum quantities apply.

Sold in full bundles only and shipped on refundable skids. Eco-Priora is available in Series 3000 and Umbriano finishes. Minimum quantities apply on custom orders. Textured surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing. Specially graded aggregates must be used for the joints. Contact Unilock for more information.

## Important Information

*Eco-Priora is the stylish permeable solution for site drainage, managing water runoff, or water harvesting projects. Paver-spacertechnology allows for joint openings which facilitate the drainage of water into the subgrade. The brushed II Campo finish on Eco-Priora makes it ideal for any application.*

**Base Requirement & Bedding Course** – open- graded or standard paver base specification.

**Handling and Installation**– A protective pad is required when doing the final paver compaction. Care must be taken to avoidtossing stones so that they bang against each other. Damage to the surface appearance can happen if handled too rough. Both random and linear patterns are common.

**Jointing Material and Joint Stabilization - permeable**

- Use only select graded stone chips for void filling
- Unilock EasyPro

**Jointing Material and Joint Stabilization - impervious**

The surface finish of Eco-Priora will determine the joint material and stabilization method. Please use recommendationsapplicable to surface type and finish.

**Sealers**

- Product may be sealed but it is not absolutely required
- Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
- Select type for desired aesthetics.
- Product must be cleaned before sealing.

**Cleaners** – Any paver cleaner may be used for color restoration or general cleaning. Follow manufacturer’s dilution rates and application procedures.

---

**i** All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call 1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.