

Cophthorne®

---

## Old world charm. New age technology.

The modern yet elegant look of Cophthorne will add a touch of class to any landscaping project. With an average compressive strength rating of up to 4 times the strength of conventional poured concrete, Cophthorne is a virtually indestructible paver that will not split, crack or fade.



### Colors



Basalt




Burgundy Red



Burnt Clay



Old Oak



Burgundy Red / Burnt  
Clay / Old Oak  
Blended on site

---

## Shapes & Sizes



Standard

20 cm x 6.5 cm x 6 cm

7.75" x 2.5" x 2.25"

---

## Why Choose **ENDURACOLOR<sup>TM</sup> PLUS**

This product features EnduraColor<sup>TM</sup> Plus, a proprietary blended layer of nature's highest performing minerals that never fade. It virtually outperforms any other paver surface when it comes to surface wear, color retention and its ability to repel even the nastiest staining substances. Choosing EnduraColor Plus, will ensure your patio, driveway, outdoor kitchen or pool deck will look like new, even after years of wear and tear.

---

[Learn About Cophthorne](#)

[Cophthorne Torture Test](#)

---

## Features

### Applications

---

Borders & Accents

Pedestrian

Residential Vehicular

### Technologies

---

#### EnduraColor™ Plus

EnduraColor Plus is the defining difference when it comes to superior wear resistance and color longevity. EnduraColor Plus is not a coating or secondary treatment, but rather a proprietary blended layer of nature's highest performing minerals (which never fade) that have been embedded right into the surface of each stone during the manufacturing process. This ensures that the surface will not fade, crack, peel or delaminate, and the beauty of your project will last a lifetime.

#### Reala™ Surface Technology

Ultra-realistic textures cast from actual natural stone, brick and cobblestones.

#### Ultima™ Concrete Technology


For heavy traffic loads, this proprietary manufacturing process creates pavers and walls with up to 4 times the strength of poured concrete.

### Surface Texture


---

Timeworn


## Patterns




**Copthorne A**  
Standard (100%)



**Copthorne B**  
Standard (100%)



**Copthorne C**  
Standard (100%)



**Copthorne D**  
Standard (100%)

## Packaging

	Sq. Ft. Bndl.	Sq. Ft. Layer	Layers Bndl.	Ln Ft Bndl. Soldier	Lbs Bndl.	Lbs Sec.	Units Bndl.
Standard - Full Bundle	89.20	11.15	8	127.9	2349	294	600
Standard - Half Bundle	44.60	11.15	4	64	1174	294	300

### Cophthorne® Old Oak, Burgundy Red, Burnt Clay

Sold Separately/Blended on Site

#### Additional Cophthorne® Information

Sold in full bundles only on a refundable skid (except specific areas of NY where half bundles are also available). Important: Textured surfaces require a buffer between the plate compactor and the paver surface to prevent scuffing. Take extra care when using Polymeric Sand with this product. Contact Unilock for information.

## Important Information

*The surface of each Cophthorne paver is uniquely cast using Realta Surface technology to capture the feel of Europe's oldest brick streets. Made with Ultima concrete, you not only get that bygone look and feel, with the assurance that Cophthorne can be used in the most demanding of applications.*

**Base Requirement & Bedding Course** – standard paver base specification

**Handling & Installation** – A protective pad is required when doing the final paver compaction. Be sure to offset joints for best appearance. Cutting is seldom required if you are installing a curvilinear walkway. Minimum radius 6 feet for curved applications. Install from multiple pallets for best color distribution.

#### Accent compatibility

- all paver applications and as accents in walls

#### Jointing Material and Joint Stabilization

Good: Ordinary dry joint sand

- Better: Unicare Polymeric Sand, Techniseal RG+, Alliance XP
- Best: Ordinary dry joint sand stabilized by a water-based or solvent based joint sand stabilizer (joint sand stabilizer/sealer may make the surface slightly slippery).

*Note:*

- Polymeric sand is often installed too high in the joint. Ensure the sand level is lower than the paver surface to allow for a three dimensional appearance.
- Alliance Gator Maxx Polymeric Sand is recommended for concrete overlays.

#### Sealers

- Product may be sealed but it is not absolutely required
- Sealers generally decrease the slip resistance of a product
- Unilock Unicare, Surebond, BP Pro and Techniseal sealers can be used.
- Semi-gloss sealers will still appear glossy on this product. Please test a stone to ensure the desired effect.
- Product must be cleaned before sealing

**Cleaners** – Any paver cleaner from Unilock, Techniseal, Surebond or BP- Pro is acceptable.

**Special note:** Other than overlay on concrete stoops and steps, you should have a bedding layer between the pavers and the poured concrete surface to avoid issues with height variance

 All measurements are nominal

Colors, product data, and availability are subject to change without notice. Please confirm all details with your local Unilock Dealer or call

1-800-UNILOCK (1-800-864-5625) for availability in your area. The colors shown should only be used as a guide. Final color selections should always be made from actual samples.