

CAMO

MARKSMAN \oplus PRO[®]

FOR COMPOSITE/CAPSTOCK/PVC



3/16" SPACING

The CAMO Marksman Pro delivers a beautiful, fastener-free surface for composite/capstock, PVC, kiln dried pressure-treated and many other kinds of decking. The Marksman Pro automatically spaces boards 3/16" and positions CAMO Hidden Fasteners for side angle entry to the deckboard. With this easy-to-use system, the beauty of the board is all you see.

CAMOFASTENERS.COM

CAMO[®]

HIDDEN DECK FASTENING SYSTEM

MARKSMAN PRO[®]

The patent-pending CAMO Marksman Pro positions CAMO Hidden Fasteners for side-angle entry to the deckboard and provides automatic 3/16" spacing. CAMO Marksman tools are designed for use with CAMO Hidden Fasteners only.

- Designed for use with composite, PVC, kiln dried treated, and other softwood lumber
- Automatic 3/16" spacing
- Fits any 5-1/4" to 5-3/4" deckboard
- Dual screw guides fasten both sides of the board with single tool placement
- Clamping action grips deckboard



DRIVER BITS

CAMO Driver Bits are engineered specifically for use with the CAMO Hidden Deck Fastening System. The built in shoulder sets automatic depth of drive for maximum holding power, and prevents over-driving the screw.



T15



- 3" Driver Bit – for use with solid, ungrooved deck boards



- 3" Grooved Board Driver Bit – with higher shoulder for deeper penetration when using grooved deck boards

HIDDEN FASTENERS



ProTech Coated



316 Stainless Steel

PROPRIETARY DESIGN – PATENT PENDING

- A reverse rake tip removes deck material as it bores, allowing the screw to penetrate the board without splitting
- A star drive offers more points of contact for better performance and reduces bit slippage and wear
- An aggressive lower thread pattern provides superior holding power while the reverse upper thread pulls the board tight to the joist and provides a clean, finished entry
- A unique trimhead design provides a less visible point of entry

CHOICES FOR CORROSION RESISTANCE/ACQ COMPATIBILITY

- ProTech Coated Carbon Steel – Three protective layers that pass a 1500 hour salt spray test in accordance with ASTM B117 and guards against corrosion when used with chemically treated wood
- 316 Stainless Steel – ultimate in corrosion resistance; recommended for coastal environments

LENGTHS

- 1-7/8" – For use with 3/4" - 1" deckboards
- 2-3/8" – For use with 1" - 1-1/2" deckboards

INDEPENDENTLY TESTED

- Exceed ICC-ES Acceptance Criteria for Deck Board Span Ratings and Guardrail Systems (Guards and Handrails) (AC174) (Section 4.1.4) in all wood, composite and PVC boards tested.

PACKAGE COVERAGE:

Based on 16" OC

- 100 COUNT = 25 SQ. FT.
- 350 COUNT = 100 SQ. FT.
- 700 COUNT = 200 SQ. FT.
- 1750 COUNT = 500 SQ. FT.

